



SECTION 1: DESCRIPTION & BENEFITS

- 4.8 mil (120 micron) smooth PVC backing with high tensile strength
- Without coating any adhesive
- Different color is available as per your requirement
- Easy for hand-tear, easy-used by workers on site
- Excellent conformity to uneven surface applications
- Excellent resistance to moisture and vapor, corrosion
- Easily wrapping on the tubes or pipes

SECTION 2: SPECIFICATIONS

Product Characteristics	Performance Data	Test Method
PVC Thickness	120 microns (4.8 mil)	PSTC-133/ASTM D3652
Material Weight	155 g/m ²	Scale
Color	Khaki, grey, blue, yellow	
Surface	Smooth, embossing	
Tensile Strength	37.5 N/25mm (8.5 Lb/In)	PSTC-131/ASTM D3759
Elongation at Break	180.0%	PSTC-131/ASTM D3759
Service Temp.	-20 ~ +80°C (-4 ~ +176 °F)	
Operating Temp.	+10 ~ +40°C(+50 ~ +105 °F)	

SECTION 3: APPLICATIONS & OTHER DETAILS

- Air conditioner pipe wrapping
- Electrical insulation
- Surface protection, moisture barriers
- Other general purpose for HVAC industry



Sliced roll width available (or customized): 45,50,72,75,96,100 mm, etc

Jumbo roll: 1000/1200 mm x 500m, etc

Tolerance: Thickness: +/- 10% Width: +/-1.0mm Length: +/- 0.4m

Storage: Indoor storage: -5°C-40°C(humidity: <80%), cool & dry, free of direct sunlight

Shelf Life: 12 months in room temp.

N.B. Please keep the operating surface clean, dry, and free of grease or other dirt & dust. So that **Egret Tape** can have a best performance.

Changzhou Egret Manufacturing Co., Ltd

No.4, Tongshun Rd, Henglin Town, Changzhou 213101 • China

T: +86 519 8878 9969 Ext. 807 Email: info@egretmfg.com Website: www.egretmfg.com