



Egret ® PU foam Tape

EGPU-8

SECTION 1: DESCRIPTION & BENEFITS

- 8mm low-density open-cell PU foam as carrier
- Coated with special formula of very high tack adhesive
- Laminated with white silicon paper easy release liner
- Excellent properties of sound dampening, cushioning
- With special net structure, good for vibration absorption
- High resilience features, suitable for padding and gasketing.
- Good vapor & moisture resistance
- Outstanding conformity to uneven surfaces




SECTION 2: SPECIFICATIONS

Product Characteristics	Performance Data	Test Method
Carrier Color	Off-White	Visual
Liner Color	White	Visual
Density	≥ 20 KG/m ³	ASTM D-3575
Peel Adhesion	≥ 6 N/CM	ASTM D-3330
Loop Tack	17 # steel ball	GB/T 4852-84
Tensile strength	13 N/CM	ASTM D3759
Elongation	≥ 130%	ASTM D-3330
Temp Resistance	-30°C~80°C	

SECTION 3: APPLICATIONS & OTHER DETAILS

- Automotive interior fixing parts
- Home appliance sound dampening
- Padding for electrical device
- Cushioning during transportation
- Thermal insulation material



Sliced roll width available (or customized): 10-1600mm

Standard Length: 100-2000mm

Tolerance: Thickness: +/- 10% Width: +/-1.0mm Length: +/- 0.4m

Storage: Indoor storage: -5°C-40°C(humidity:<80%), cool & dry, free of direct sunlight

Shelf Life: 12 months in room temp.

N.B. Please keep the operating surface clean, dry, and free of grease or other dirt & dust. So that **Egret Tape** can have a best performance.

审批
2022.07.26

Changzhou Egret Manufacturing Co., Ltd

No.4, Tongshun Rd, Henglin Town, Changzhou 213101 • China

T: +86 519 8878 9969 Ext. 807 Email: info@egretmfg.com Website: www.egretmfg.com